



PIS100 & PIS200 Product Specifications

| Model Name | PIS100 1-Port PoE DC Injector with Surge Suppressor | PIS200 2-Port PoE DC Injector with Surge Suppressor |
|-------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Product Dimensions (WxHxD): 70x48x24mm |  |  |
| No. of Power Injector Ports | 1 | 2 |
| Total No. of Ports | 2 | 2 |
| Surge Protection | Yes | Yes |
| Data Line Tx/RX Crossover | Yes | Yes |
| Max Operating Voltage | 48VDC | 48VDC |
| Data Clamp Voltage | 7.5VDC | 7.5VDC |
| Power Clamp Voltage | 60VDC | 60VDC |
| Data Transfer Rate | 100mbps | 100mbps |
| Protection Mode | Line-Line and Line-GND | Line-Line and Line-GND |
| Response Time | < 5 ns | < 5 ns |
| Max Shunt Capacitance | < 25 pF | < 25 pF |
| PoE Pins Protected | All 8 | All 8 |
| Peak Pulse Current (10/1000uS) | Pins: 1,2,3,6 = 132A Pins: 4,5,7,8 = 100A | Pins: 1,2,3,6 = 132A Pins: 4,5,7,8 = 100A |
| RJ45 Port | Metal Shielded | Metal Shielded |
| RJ45 Port | Metal Shielded | Metal Shielded |
| Temperature | -40°C to +85°C | -40°C to +85°C |
| Humidity | 0 ~ 90% RH | 0 ~ 90% RH |
| Ground Wire | 16 AWG, 10" Long | 16 AWG, 10" Long |
| Ground Screw | Yes | Yes |
| Power Fuse | 1.5A | 1.5A |
| Warranty | 2 Years | 2 Years |