InscapeData

Total PoE Solutions for Wired/Wireless, IP Video, & Smart City Applications

OUTDOOR POE PLUS GIGABIT DC POWER INJECTOR

LinkPower™ tL{2лЗл Зл ² млкмллкмллл a ōLJă 2π t2ℕŰ DλƎl·ōλŰ t29 Ly?ŜŎű2ℕ

Inscape Data's LinkPower™ PIS2030 two LJ2ℕŰ млкмллкмллл a t29 (Power over Ethernet) Iy?ŜŎű2ℕ λă l· ƎλƎl·ōλŰ KλƎK LJ2ǿŜℕ 30W DC t29 λy?ŜŎű2ℕΣ l·yŘ λŰ ădzLJLJ2ℕűă L999 улнΦol·ŦK L999улнΦol·ú, PoE+ ăűl·yŘl·ℕŘsΦ ¢KŜ Y'l·ÈλY'dzY' 2dzűLJdzű LJ2ǿŜℕ λă Зл ² Σ and úKŜ total system LJ2ǿŜℕ λă 45 ² Φ ¢KŜℕŜ l·ℕŜ two wWnp ySűǿ2ℕ] LJ2ℕúăΣ and 2yŜ 2Ŧ ǿKλŎK λă dzăŜŘ l·ă an dzLJfλy] port to a ăǿλúŎK 2ℕ to another ySűǿ2ℕ] ŘŜØλŎŜΦ !y2úKŜℕ ySűǿ2ℕ] LJ2ℕŰ λă úKŜ PoE LJ2ℕŰ úKl·ú λyúŜƎNl·ŰŜŘ t29 LJ2ǿŜℕ 2dzűLJdzű l·yŘ ySűǿ2ℕ] Řl·úl·Φ The 30W power DC output simplifies the overall λyăűl·ffl·ûλ2y' by eliminating the need for a power cord, such as, KλƎK LJ2ǿŜℕ ySűǿ2ℕ] Ř2Y'Ŝ Ŏl·Y'ŜℕI·ă 2ℕ 2úKŜℕ KλƎK LJ2ǿŜℕ Lt ŘŜØλŎŜăΦ

Key Features & Benefits

- Supply power to 5 classes Ethernet network surveillance cameras
- нÈ млкмллкмллл a ōLJă wWnp LJ2ℕűă
- {dzLJLJ2ℕŰ ySűǿ2ℕ] LJ2ℕúΣ fλƎKűyλyƎπLJℕ22Ŧ LJ2ǿŜℕ λyLJdzú LJ2ℕŰ ŏúKŜ ăŜŎ2yŘl·ℕè fλƎKűyλyƎ LJℕ2ŰŜŎűλ2yŰ
- t29 LJ2ǿŜℕ ădzLJLJfè ŰèLJŜ λă Ŧ2dzℕ fλySˆ LJl·λℕă 2Ŧ ŰǿλăűŜŘ LJl·λℕΣ ûKŜ LJ2ăλúλØŜ LJ2ǿŜℕ ădzLJLJfè ăλŘŜ λă мкн 2ℕ пкр fλySˆ LJl·λℕΣ l·yŘ úKŜ ySƎl·ûλØŜ LJ2ǿŜℕ ădzLJLJfè ăλŘŜ λă окс 2ℕ тку fλySˆ LJl·λℕ
- {dzLJLJ2ℕŰ L999улнΦol·ŦкL999улнΦol·ú ăűl·yŘl·ℕŘs
- Single LJ2ℕŰ PoE 2dzűLJdzű LJ2ǿŜℕ λă 3л ² Σ output Ø2fűl·ƎŜ λă п5.6ЧрЗ.8± Σ l·yŘ úKŜ û2űl·f LJ2ǿŜℕ λă 45 ²
- b2 Ŧl·yãΣ yl·údzℕl·f Ŏ22fλyƎΣ ăYˆl·ff l·yŘ ŜÈljdzλăλűŜΣ y2 y2λăŜ ŘŜăλƎyΣ ădzλűl·ōfŜ Ŧ2ℕ 2dzűŘ22ℕ λyãűl·ffl·ûλ2y'
- Ltcтғ /2Y'LJfλl·yű wl·úλyƎ !yŘ ² l·úŜℕ ¢λƎKű /2yŷŜŎú2ℕă .l·ăŜŘ hy'tl·ûŜyű tŜyŘλyƎ ¢ŜŎKy2f2Ǝè
- 9ÈűŜℕyl·f [95ă π lλƎKfè ±λăλōfŜ [95 LyŘλŎl·ú2ℕ Ŧ2ℕ 9ŰKŜℕySű [λy]Σ t29 t2ǿŜℕΣ {èăűŜY' t2ǿŜℕΣ ϑ ! / hdzűLJdzű t2ℕŰΦ

* When used with the included watertight connector kit

Applications

- *Smart City*
- *IP Video Surveillance*
- *Campus Network*
- *Wireless Mesh Network*
- *Border Security Surveillance*
- *Municipal Network*
- *Energy & Refineries*
- *Hospitality Network*
- *Hotel Resort Network*
- *Hotspot Integration*
- *VOIP Service*
- *Traffic Monitoring*

System Configurations



[1]Voltage Status can be 12V DC, 24V DC, 48V DC, or 802.3af depending on the models.

All above images were taken for the purpose of these explanations; actual images may differ. (03/2023-T)

Product Name	10/100/1000M 30W Two Port PoE Injector
Product Model	PIS2030
Port Description	1x AC Input Port 1x RJ45 Data input port, 1x RJ45 PoE output port
PoE Power Supply	mid-span: 4/5, 7/8 data line pair(default); end-span: 1/2,3/6 spare line pair (can be customized)
Network Medium	1000BASE-TX: 5Cat and more UTP (≤100 meters)
Thermal Protection	>100°C
Performance	Working Rate:10/100/1000Mbps
	Network port protection: meet with IEC61000-4-2(ESD)
	MTBF: 100,000 hours
PoE Standards	IEEE 802.3af/at, PoE+
LEDs Indicator	PoE working status
Power	Total system power: 45W
	PoE port power: 30W (IEEE802.3af/at, PoE+)
	Input Voltage: 120V ~240V AC
Dimensions/Weight	LxWxH: 193.80mm x 117.60mm x 78.49mm (7.63x4.63x3.09 inch) / 4LB / 1.6kg
Working Environment	Operating Temperature: -30°～ 70°C , Storage Temperature: -20°～ 75°C
	Working Humidity: 10%～90%, non-condensing Storage Humidity: 10%～95%, non-condensing
Safety & EMC	CE mark, commercial, FCC Part 15 Class B, RoHS UL60950-1, TUV EN60950-1 Approved
Warranty	3-year warranty



PD and PSE Eight-Pin RJ45 Modular Jack

PSE Pinout			PD Pinout	
RJ45 Conductor Pin#	802.3af Mode A	802.3af Mode B/ Passive PoE*	802.3af Mode A	802.3af Mode B/ Passive PoE*
1	Rx, V+	Rx	TX+, V+	TX+
2	Rx, V+	Rx	TX-, V+	TX-
3	Tx, V-	Tx	RX+, V-	RX+
4	Spare	V+		V+
5	Spare	V+		V+
6	Tx, V-	Tx	RX-, V-	RX-
7	Spare	V-		V-
8	Spare	V-		V-

PACKAGE CONTENTS

- **PIS2030** (1)
- WECK0001 Waterproof Ethernet Connector Kit (1)
- WPCK0001 Waterproof Power Cord Kit (1)
- User Manual (1)
- 3-Year Warranty Sheet (1)
- MMK0001-XS Pole Mount Kit (1) (Optional)

InscapeData

United States Headquarters 2012 Hartog Drive, CA 95131, U.S.A.
PHONE +1.408.392.9800 TOLL FREE +1.888.267.4507 FAX +1.408.392.9812
EMAIL sales@inscapedata.com
Revision 1.0

© Copyright 2023, Inscape Data Corporation, All Rights Reserved. LinkPower and Inscape Data are trademarks of Inscape Data Corporation
Disclaimer: While every effort is made to ensure the information given is accurate, Inscape Data Corporation does not accept liability for any errors or mistakes which may arise. All specifications are subject to change without notice.